Full Color Mailer Box
- Double Sided 8 x 6 x 4 in

Material colour	white
Colour space	CMYK
Print areas	outside + inside
Outside dimensions	8 x 6 x 4 in

Make sure that all the blacks in your design have CMYK value: C:0% M:0% Y:0% K:100%

Packhelp

In case of any doubt contact us via chat or at contact@packhelp.com

outside

inside

PLEASE DO NOT MODIFY THE DIELINE IN ANY WAY

Your checklist

For the best quality and smooth production, please make sure your project meets our specification and use the checklist.

- [ ] **Bleed and Margin**
  Include a 1/4-inch bleed beyond the die line on all edges and glue flap.
  Margins, rule outlines, and copy need to be at minimum 1/8-inch inside of all die line edges and scores.
- [ ] **Image Resolution**
  For best results, all artwork and image resolution should be no less than 300dpi.
- [ ] **Placed Graphics**
  Always place graphics at 100%.
  Ensure all graphic components are placed within your artwork layer(s), not the die line layer.
  Artwork placed on the die line layer may be inadvertently deleted during our prepress process.
- [ ] **Raster vs. Vector Art**
  Combining raster and vector artwork with the same CMYK color build can result in different final print appearance. Artwork that uses the same CMYK build should be built either as all vector or all rasterized images to avoid any possible color shifts.
- [ ] **Color Profile**
  Art files should be built as CMYK. RGB images and PMS colors will be converted to CMYK, which can greatly affect the color of print.
- [ ] **Technical Spot Colors**
  Do not use technical spot colors (Cut, Crease, Annotations, Dimensions) in your artwork.
- [ ] **Technical Spot Colors**
  Do not use technical spot colors (Cut, Crease, Annotations, Dimensions) in your artwork. These colors are meant to be used for the die line only. Using the technical spot colors in your artwork could cause artwork that uses technical spot colors to not print.
- [ ] **Lines and Strokes**
  Minimum thickness for positive lines: .25pt.
  Minimum thickness for reverse lines: .75pt.
- [ ] **Text and Fonts**
  Please proofread all text carefully. We are not financially responsible to fix client-supplied typos.
  Minimum text size for positive text: 4pt
  Minimum text size for reverse text: 6pt.
  Point size may need to be larger or a heavier weight used based on individual font characteristics.
  When reversing type, use one weight heavier than weight intended to use.
  Avoid using small trademark (™) and register mark (®) symbols to print in reverse as they may fill.
  Convert all text to outlines
  Do not set text components to overprint. Overprint text may disapear in the final print result.
- [ ] **Ink Saturation**
  Black Ink: Too much ink in any one area can lead to printing or drying issues.
  Rich Black: If your art includes black, we recommend a rich black build of 30C/30Y/30M/100K.
  For best results, include a .5pt. stroke of 100% black (K) to avoid print overspray.
  Black Text: We recommend 100% black (K) for small black text.
- [ ] **UPCs and Barcodes**
  If intended to be scanned, UPC-A type barcodes need to be at least 150% size (approx. 2.2-inch wide). For proper scanning, the height of the bars is recommended to be at least .5-inch tall. Barcodes should be designated as 100% black (K) for best scanning results.